

UNI-H4 (WIFI)

Face Recognition Terminal

OVERVIEW

The Uni-H4 (Wi-Fi) face recognition terminal adopts a deep learning algorithm, which helps to recognise the face faster with higher accuracy.

It also supports multiple authentication modes: face and MIFARE card authentication.

It has an IP65 rating and can be applied in multiple scenarios including outdoor areas and areas with high dust levels.

The terminal supports a Wi-Fi connection.



Facial Recognition



MIFARE Card



Wi-Fi Enabled



HARDWARE		CAPACITY	
Display	4.3 inch	Card	3,000
Type	LCD	Face Template	3,000
Operation Method	Capacitive Touch Screen	Log	150,000
AUDIO		Card Type	Mifare 1 card
Tone quality	Noise suppression and echo cancellation	Card Reading Frequency	13.56 MHz
NETWORK		Face recognition accuracy rate	> 99%
Wired Network	10M / 100M self-adaptive	Face recognition duration	< 0.2 s
Wi-Fi	Supported	Face Recognition Distance	0.3 to 1.5m
VIDEO		OPERATING CONDITIONS	
Pixel	2MP	Temperature	-30°C to 60°C
Lens	x2	Humidity	0 to 90% (non-condensing)
FUNCTION		Power Supply	12VDC / 2A
QR code recognition	Supported	Power Supply Method	2 pin connector
Face anti-spoofing	Supported	Button	Touch Screen
Audio prompt	Supported	Dimensions	172.5 mm × 83.2 mm × 22.7 mm
Time synchronization	Supported	Installation	Surface mounting

We've offered proudly South African developed solutions since 1945 for the local and international market. Our easy to use solutions are configured to your requirements to ensure total accuracy. Uniclox is your One-Stop Shop in Turnkey Solutions, ensuring peace of mind.



300 Hennie Alberts Street
Alrode South, Alberton, 1451



011 439 2000



sales@uniclox.com
www.uniclox.co.za