

## UNI-H3 (POE)

**Face Recognition Terminal** 

## **OVERVIEW**

The Uni-H3 face recognition terminal adopts a deep learning algorithm, which helps to recognize the face faster with higher accuracy. It supports multiple authentication modes: face/card authentication and also supports Wi-Fi. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas. Power is supplied by a standard PoE and at the same time supplies power for a door lock (12 VDC/1 A).







Facial Recognition

Card Recognition

Wi-Fi Enabled

| SYSTEM               |                            | CAPACITY                       | HIKVISION  |
|----------------------|----------------------------|--------------------------------|--|
| Operating System     | Linux                      | Card                           | 3,000  |
| DISPLAY              |                            | Face                           | 1,500  |
| Dimensions           | 4.3-inch                   | Event                          | 150,000  |
| Resolution           | 272 x 480                  | AUTHENTICATION                 |  |
| Type                 | LCD                        | Card Type                      | Mifare 1 card  |
| Operation Method     | Capacitive Touch Screen    | Card Reading Frequency         | 13.56 MHz  |
| VIDEO                |                            | Face Recognition Duration      | < 0.2 s  |
| Pixel                | 2MP                        | Face Recognition Accuracy Rate | > 99%  |
| Lens                 | x 2                        | Face Recognition Distance      | 0.3 to 1.5 m   |
| Video Standard       | PAL (default) & NTSC       | GENERAL                        |  |
| FUNCTION             |                            | Power supply                   | Power input: Power interface (power adapter included, 12 VDC/1 A) or PoE (37 to 57 VDC/0.6 A). Power output: Power supply for door lock, 12 VDC/1 A (only when the device is powered by PoE supporting powering supply for door lock). |
| Face Anti-spoofing   | Support                    |                                |  |
| Audio Prompt         | Support                    |                                |  |
| Time Synchronization | Support                    | Working Humidity               | 0 - 90% (no condensing)  |
| NETWORK GENERAL      |                            | Working Temperature            | -30 °C to 60 °C  |
| Wired Network        | 10 M/100 M self-adaptive   | Working Humidity               | 0 - 90% (no condensing)  |
| OTHER                |                            | Dimensions                     | 91.3 x 181.3 x 24.5 mm   |
| Software             | Vision Enterprise Platinum | Protective Level               | IP65   |
| POE                  | IEEE802.3at, standard PoE  | Installation                   | Wall Mounting  |

We've offered proudly South African developed solutions since 1945 for the local and international market. Our easy to use solutions are configured to your requirements to ensure total accuracy. Uniclox is your One-Stop Shop in Turnkey Solutions, ensuring peace of mind.





