

UNI-H3 (POE)

Face Recognition Terminal

OVERVIEW

The Uni-H3 face recognition terminal adopts a deep learning algorithm, which helps to recognize the face faster with higher accuracy. It also supports multiple authentication modes: face/card/fingerprint authentication, etc. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas. Power is supplied by a standard PoE and at the same time supplies power for a door lock (12 VDC/1 A).



Facial Recognition



Card Recognition



SYSTEM		CAPACITY	
Operating System	Linux	Card	3,000
DISPLAY		Face	1,500
Dimensions	4.3-inch	Event	150,000
Resolution	272 x 480	AUTHENTICATION	
Type	LCD	Card Type	Mifare 1 card
Operation Method	Capacitive Touch Screen	Card Reading Frequency	13.56 MHz
VIDEO		Face Recognition Duration	< 0.2 s
Pixel	2MP	Face Recognition Accuracy Rate	> 99%
Lens	x 2	Face Recognition Distance	0.3 to 1.5 m
Video Standard	PAL (default) & NTSC	GENERAL	
FUNCTION		Power supply	Power input: Power interface (power adapter included, 12 VDC/1 A) or PoE (37 to 57 VDC/0.6 A). Power output: Power supply for door lock, 12 VDC/1 A (only when the device is powered by PoE supporting powering supply for door lock).
Face Anti-spoofing	Support	Working Humidity	0 - 90% (no condensing)
Audio Prompt	Support	Working Temperature	-30 °C to 60 °C
Time Synchronization	Support	Working Humidity	0 - 90% (no condensing)
NETWORK GENERAL		Dimensions	91.3 x 181.3 x 24.5 mm
Wired Network	10 M/100 M self-adaptive	Protective Level	IP65
OTHER		Installation	Wall Mounting
Software	Vision Enterprise Platinum		
POE	IEEE802.3at, standard PoE		

We've offered proudly South African developed solutions since 1945 for the local and international market. Our easy to use solutions are configured to your requirements to ensure total accuracy. Uniclox is your One-Stop Shop in Turnkey Solutions, ensuring peace of mind.



300 Hennie Alberts Street
Alrode South, Alberton, 1451



011 439 2000



sales@uniclox.com
www.uniclox.co.za