

UNI-H4 (F) WIFI

Face & Fingerprint Recognition Terminal

OVERVIEW

The Uni-H4 (F) WIFI face and fingerprint recognition terminal adopts a deep learning algorithm, which helps to recognise the face faster with higher accuracy.

It also supports multiple authentication modes: face, fingerprint and MIFARE card authentication.

It has an IP65 rating and can be applied in multiple scenarios including outdoor areas and areas with high dust levels.

The terminal supports a Wi-Fi connection.



Facial Recognition



Fingerprint Recognition



MIFARE Card



Wi-Fi Enabled



HARDWARE		CAPACITY	
Screen Size	4.3 inch	Card	3,000
Resolution	272 x 480	Fingerprint	3,000
Operation Method	Capacitive Touch Screen	Face Template	3,000
NETWORK		Log	150,000
Wired Network	10M / 100M self-adaptive	Card Type	Mifare 1 card
Wi-Fi	Supported	Face Recognition Duration	< 0.2 s
VIDEO		Face Recognition Distance	> 2m
Pixel	2MP	OPERATING CONDITIONS	
Lens	x2	Temperature	-30°C to 60°C
FUNCTION		Power Supply	12VDC to 24 VDC / 2A
Face anti-spoofing	Supported	Protective Level	IP65
Audio prompt	Supported	Dimensions	172.5 mm × 83.2 mm × 22.7 mm
Live view	Supported	Installation	Surface mounting

We've offered proudly South African developed solutions since 1945 for the local and international market. Our easy to use solutions are configured to your requirements to ensure total accuracy. Uniclox is your One-Stop Shop in Turnkey Solutions, ensuring peace of mind.





